




T-LINK
RECORD, DISPLAY
AND ANALYSE DATA

**COMPACT CRUSHING,
SCREENING & CONVEYING
EQUIPMENT**



EvoQuip offers a comprehensive range of crushing, screening and conveying products to suit a wide variety of industries. The EvoQuip range includes jaw and impact crushers, scalping and incline screens as well as a variety of conveying equipment.



BUILDING & CONSTRUCTION

EvoQuip machines are easy to transport and can come directly to your site to crush and screen the waste from your demolition projects. Onsite recycling allows you to turn your existing waste into reusable and sellable products increasing your profits and reducing your carbon footprint.



AGRICULTURE & LANDSCAPING

EvoQuip equipment can offer agricultural contractors an opportunity to diversify in the off season, helping to retain staff and ensure a steady workload throughout the year. When you are not farming use EvoQuip equipment to demolish old farm buildings, process material for lanes, driveways and drainage stones. Certain models in the range can be transported on an agricultural trailer.

Due to the very compact dimensions of EvoQuip equipment it can overcome access issues due to narrow lanes and country roads. The equipment can come directly to your home to screen top soil for home gardens or golf courses; crush material from worn driveways and brick walls.



QUARRIES

EvoQuip machines can be used in small to medium sized quarries to process natural material into sellable products. With optional add ons it is possible to produce a variety of aggregates in a single step.



RECYCLING

EvoQuip equipment provides the ideal solution for generating profit from waste. It is possible to process many types of waste from C&D, asphalt, concrete rubble to washout, producing and segregating sized products. This waste can then be reused as product on site or sold, resulting in reduced transport and emissions of bringing material to site; avoiding waste disposal costs and reducing virgin material used.



PLANT HIRE

The versatility and compact nature of the EvoQuip range creates a natural addition for plant & tool hire companies. With the ease of use and weights ranging from 3.2 tonnes to 28 tonnes, the EvoQuip machines are suitable for rental into everything from light residential to heavy commercial use.

GRUSHERS



CRUSHING RANGE

BISON 280



HOPPER / FEEDER

3.6m³ (4.7yd³) Hopper capacity

Two stage grizzly feeder as standard

50mm (2") Nominal spacing grizzly

JAW CRUSHER

900mm x 600mm (36"x24") Jaw inlet

Min CSS: 40mm (1.5") Recycle / 50mm (2") in natural rock

Max CSS: 130mm (5")

Hydraulic jaw adjustment

POWERUNIT

Tier 3: CAT C7I 140kW (187Hp)

Tier 4 Final: Caterpillar C4.4 129kW (173Hp)

Stage V: Caterpillar C4.4 129 kW (173hp)

Direct drive to crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 200 tph / 220 US tph

CONVEYORS

800mm (32") Wide product conveyor

Product conveyor discharge height: 2.9m (9'6")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	12.4m (40' 8")	2.4m (7' 10")	3.2m (10' 6")

Weight: Tier 3: 27,700kgs (61,068lbs)

Tier 4F: 27,500kgs (60,627lbs)

*including dirt conveyor and magnet

CRUSHING RANGE

BOA 950



HOPPER / FEEDER

Hopper length: 2.67m (8' 7")
Hopper width: 2.2m (7' 2")
Hopper capacity: 2.9m³ (3.8yd³) (standard)
3.9m³ (5.1yd³) (optional)
5.3m³ (6.9yd³) (optional)

Wear resistant feed hopper
Feed Conveyor belt Width: 1000mm (39")
Over and under belt metal detector

CONE CRUSHER

TC 1000 Automax cone chamber
Concave: Medium coarse (Standard)
Maximum feed size: 160mm
Min CSS: 18mm (0.7")*
Max CSS: 36mm (1.4")*

POWERUNIT

Tier 3/Stage 3A: CAT C9.3 ACERT 250kW (335hp)
Direct drive to crusher via clutch
Fuel tank capacity: 552 L (137 US Gal)

OUTPUT POTENTIAL

Up to 220 tph / 242 US tph

PRODUCT CONVEYOR

Product conveyor width: 800mm (32")
Discharge height: 3.25m (10' 8")

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	12.86m (42' 3")	2.8m (9' 2")	3.46m (11' 4")

Weight: Tier 3: 31,100kgs (68,564lbs)

CRUSHING RANGE

COBRA 290



HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper capacity
Integrated pre-screen for fines removal
Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

1030mm (41") x 790mm (31") Crusher Inlet
1000mm (40") Wide x 1034mm (41.5") diameter rotor
2 High / 2 Low configuration as standard
Max OSS – 150mm (6") upper; 75mm (3") lower
Min CSS – 50mm (2") upper; 20mm (0.75") lower
Hydraulic adjust and hydraulic overload protection as standard
Hinged crusher inlet lid as standard

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)
Tier 4 Final: Volvo D8 235kW (315Hp)
Stage V: Volvo D8 235kW (315Hp)
Direct drive to crusher via Clutch and V Belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") Wide product conveyor
Product conveyor discharge height: 3.42m (11' 3")

GENERAL

Intuitive 'Push Button' Control System

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	9.92m (32' 6")	2.55m (8' 4")	3.16m (10' 4")

Weight (with Magnet): Tier 3: 28,700kgs (63,273lbs)
Tier 4F: 28,700kgs (63,273lbs)

CRUSHING RANGE

COBRA 290R

HOPPER / FEEDER

3.3m³ (4.3yd³) Hopper capacity
Integrated pre-screen for fines removal
Feeder speed auto-regulates depending on crusher load

IMPACT CRUSHER

1030mm (41") x 790mm (31") crusher inlet
1000mm (40") x 1034mm (41.5")
Max OSS - 150mm (6") upper, 75mm (3") lower
Min CSS - 50mm (2") upper, 20mm (3/4") lower
2 high / 2 low configuration as standard
Hydraulic adjust and hydraulic overload as standard

SCREEN

2.74m x 1.5m (9'x5') single deck screen
Wide range of screen media
Side tensioned
Screen can be lowered to horizontal to ease mesh change and maintenance

POWERUNIT

Tier 3 Equivalent: Volvo D8 235 kW (315hp)
Tier 4 Final: Volvo D8 235kW (315Hp)
Stage V: Volvo D8 235kW (315Hp)
Direct drive to crusher via clutch and V belts

OUTPUT POTENTIAL

Up to 290tph / 320 US tph

CONVEYORS

1000mm (40") Wide product conveyor
500mm (20") Wide side conveyor (option)
Side conveyor (option) discharge height 2.48m (8'2")
500mm (20") Transfer conveyor
500mm (20") Oversize conveyor with Recirc & Stockpile.
1200mm (47") Fines conveyor with 3m (9'10") discharge

GENERAL

Intuitive 'Push button' control system
Afterscreen system is quick to detach

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	14.76m (48' 5")	2.9m (9' 6")	3.16m (10' 4")

Weight (with Magnet): Tier 3: 34,200kgs (75,398lbs)
Tier 4F: 34,200kgs (75,398lbs)



SCREENERS



SCREENING RANGE

COLT 600



FEEDER

3m³ (3.9yd³) Hopper capacity
1m (40") Wide
Variable speed
Maximum feed size: 300mm (12")

SCREEN

2.34m x 1.17m (8' x 4') Double deck screen
Wide range of screen media
Top Deck - Bofor Deck, Fingers, Punch Plate & Mesh
Bottom Deck - Mesh & Fingers

POWERUNIT

Tier 3: CAT 2.2 45.5kW (61Hp) @ 1780 RPM
Tier 4F / Stage IV: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM
Stage 5: Deutz TD2.9L4 - 42kW (56 Hp) @ 1900 RPM

OUTPUT POTENTIAL

Up to 280 tph / 308 US tph

CONVEYORS

650mm (26") Wide fines conveyor with 2.9m (9'6") discharge
650mm (26") Wide midgrade conveyor with 2.8m (9'2") discharge
1000mm (40") Wide oversize conveyor with 2.7m (8'10") discharge
Variable speed on midgrade and oversize as standard
Ability to convert to 2 way split

TRANSPORT

Containerisable
Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	10.98m (36')	2.25m (7' 5")	2.55m (8' 4")

Weight (standard machine): 12,000kgs (26,455lbs)



SCREENING RANGE

COLT 1600



FEEDER

7m³ (9.16yd³) Hopper capacity
Heavy Duty Apron Feeder
2600mm (8' 6") wide
Variable speed

SCREEN

4.8m (16') x 1.5m (5') Double deck screen
Variable Speed
Hydraulic adjust screen angle
Single Shaft, Triple Shaft and Spaleck screenbox options
Wide range of screen media
Standard & Triple Shaft:
Top Deck: Fingerscreen, Punchplate, Bofar Deck, Woven Mesh
Bottom Deck: Fingerscreen & Woven mesh
Spaleck:
Top Deck: 3D Punchplate "Church Window, Metal & Rubber"
Bottom Deck: Flip flow Technology

POWERUNIT

Tier 3: CAT C4.4 - 83kW (111.3hp) @ 1800rpm
Tier 4F/Stage V: Deutz TCD 3.6L4 - 92kW (123hp) @ 1800rpm
Hybrid option - 2 x37kW IE3 electric motors
c/w hydraulic gear pumps and electrical control panel
Easy access for maintenance

OUTPUT POTENTIAL

Up to 600 tph / 672 US tph

CONVEYORS

1200mm (48") Wide collection conveyor
900mm (35") Wide fines conveyor with 4.0m (13'1") discharge
800mm (32") Wide midgrade conveyor with 3.4m (11'2") discharge
1200mm (48") Wide oversize conveyor with 3.6m (11'10") discharge
Configurable layout and ability to convert to 2 way split
Variable speed on fines, midgrade and oversize as standard
Telescopic conveyor & Chassis Extension (300mm / 12" riser) options

TRANSPORT

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	14.95m (49' 1")	3.0m (9' 10")	3.4m (11' 2")

Weight: 31,000kgs (68,342lbs) Single shaft std configuration
34,000kgs (74,956lbs) triple shaft std configuration



CONVEYORS



CONVEYOR RANGE

TC65



CONVEYOR

Conveyor Length: 19.79m (64'11")

Belt Width: 1050mm (42")

Max Discharge Height @ 28°: 9.45m (31')

Capacity: Up to 500tph (551 US tph)

Hydraulic Folding Head Section

Belt Type: Plain - 3 Ply

Feedboot with removable 6mm wear liners

Variable speed control

Pinless Deployment

POWERUNIT

Tier 3: CAT 2.2 55kW (74hp)

Tier 4F: Deutz TD2.9 45kW (60hp)

Stage V: Deutz TC 2.9 L4 45kW (60hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.3m (37')	2.25m (7' 4")	2.65m (8' 8")

Weight: 13,820kgs (30,467 lbs)

Containerised shipping 40' x 9'6"

High Cube Container



CONVEYOR RANGE

TC80

HYBRID

CONVEYOR

Conveyor Length: 22.8m (74' 10")
Belt Width: 1050mm (42")
Max Discharge Height @ 25°: 10.41m (34' 1")
Capacity: Up to 500 tph (551 US tph)
Hydraulic Folding Head Section
Belt Type: Plain - 3 Ply
Feedboot with removable 6mm wear liners
Variable speed control
Pinless Deployment

POWERUNIT

Tier 3: CAT 2.2 55kW (74hp)
Tier 4F: Deutz TD2.9 45kW (60hp)
Stage V: Deutz TC 2.9 L4 45kW (60hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.88m (38' 11")	2.25m (7' 4")	2.88m (9' 5")

Weight: 16,750kgs (36,927lbs)
Containerised shipping 40' x 9'6"
High Cube Container



CONVEYOR RANGE

TC100

CONVEYOR

Conveyor Length: 30.1m (98' 9")
Belt Width: 1050mm (42")
Max Discharge Height @ 25°: 13.1m (43' 11")
Capacity: Up to 600 tph (661 US tph)
Hydraulic Folding Head Section
Belt Type: Plain - 3 Ply
Feedboot with removable 6mm wear liners
Variable speed control
Pinless Deployment

POWERUNIT

Stage 3A: CAT C4.4 83kW (111hp)
Tier 4F: CAT C4.4 82kW (110hp)
Stage V: CAT C2.2 55kW (73hp)

CURRENT OPTIONS

Various options available

TRANSPORT DIMENSIONS

Transport dimensions

	LENGTH	WIDTH	HEIGHT
Track Unit	11.9m (39')	2.8m (9' 4")	3.43m (11' 3")

Weight (Est): 21,800kgs (48,060lbs)
Containerised shipping 40' x 9'6"
High Cube Container



CONVEYOR RANGE

HLF50 HIGH LEVEL FEEDER

CONVEYOR

Conveyor Length: 15.6m (51' 2")
Belt Width: 1050mm (42")
Conveyor Drive: variable speed
Max. Discharge Height: 7.2m (23'8")
Capacity: up to 450 tph (496 US tph)
Hydraulic fold over for transport
Automatic greasing cartridges at head drum
Pinless Deployment
Rapid set up time

POWERUNIT

Tier 3 Engine: CAT 4.4 Power rating: 62kW (83hp)
Stage V Engine: CAT 2.2 Power rating: 55kW (75hp)

HOPPER/FEEDER

Capacity (with tipping grid): 3.8m³ (4.97 Cu.Yd.)
Capacity (Without Tipping Grid): 4.2m³ (5.5 Cu. Yd.)
Single Deck Vibrating Grid: 3.1m x 2.45m (10' 2" x 8')

CURRENT OPTIONS

Hopper upgrade
Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)
40' x 9' 6" High Cube Container

	LENGTH	WIDTH	HEIGHT
Track Unit	12.16m (39' 11")	2.29m (7' 6")	2.55m (8' 4")

Weight (Standard): 12,500kgs (27,557lbs)



CONVEYOR RANGE

LLF50 LOW LEVEL FEEDER

CONVEYOR

Conveyor Length: 15.6m (51' 2")
Belt Width: 1050mm (42")
Conveyor Drive: variable speed
Max. Discharge Height: 7.37m (24' 2")
Capacity: up to 450 tph (496 US tph)
Hydraulic fold over for transport
Hydraulic discharge height adjustment
Pinless Deployment
Rapid set up time

POWERUNIT

Tier 3 Engine: CAT 4.4 Power rating: 62kW (83hp)
Stage V Engine: CAT 2.2 Power rating: 55kW (75hp)

HOPPER/FEEDER

Capacity: 7m³ (9.2yds³)
Feed height: 2700mm (8' 9")
Hydraulic folding hopper flares
Target area flares down: 4.07m (13' 4") long x 2.1m (6' 9") wide
Target Area flares up: 1.07m (3' 5") long x 3.3m (10' 8") wide

CURRENT OPTIONS

Adjustable feed hopper outlet door
Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)
40' x 9' 6" High Cube Container

	LENGTH	WIDTH	HEIGHT
Track Unit	12.2m (40' 1")	2.77m (9' 1")	2.55m (8' 4")

Weight (Standard): 13,240kgs (29,189lbs)



CONVEYOR RANGE

WC80 RADIAL



CONVEYOR

Conveyor Length: 22.85m (74' 10)
Belt Width: 914mm (36")
Conveyor Drive: Hydraulic or Electric
Max. Discharge Height: 9.95m (32' 7") @ 23°
Capacity: up to 300 tph (336 US tph)
Pinless Deployment
Rapid set up time

POWERUNIT

CAT 1.7T Power rating: 18.4kW (24hp)
Electric drive: 15kW

FEEDBOOT

Capacity (Low Level): 0.35m³ (0.43 yd³)
Feed in Width (Low Level): 775mm (2' 6.5")
Minimum Feed In Height (Low Level) (7°): 1534mm (5')
Capacity (Extended): 1.1m³ (1.4 Cu. Yd.)
Feed in Width (Extended): 1658mm (5' 2")
Extended Minimum Feed in Height (7°): 1793mm (5' 10")

CURRENT OPTIONS

Road Towable Available
Various options available

TRANSPORT DIMENSIONS

Roll on Roll off transport (RoRo)
2x WC80 per 40' x 9' 6" High Cube Container

	LENGTH	WIDTH	HEIGHT
Road Towable (US only)	16.17m (52' 11")	2.5m (8' 3")	3.36m (11')
Pit Portable	16.55m (54' 3")	3.1m (10' 2")	3.95m (12' 11")

Weight (with full options): 10,000kgs (22,046lbs)



ADDING VALUE TO YOUR BUSINESS



Terex Financial Services (TFS) is fully integrated into the fabric of the Terex Business

We are committed to working with our dealers and customers in developing and adding true value to their business, and assisting in the acquisition and funding of their Terex equipment.

TFS offer global solutions and through a team of dedicated people who understand the needs of our dealers and customers we can direct you to the correct financial solution for your business.

We have developed a Turnkey Funding solution to assist our dealer partners, this offer is designed to maximize a dealers potential to develop their Terex Business.

- Terex Self-funding Capability
- Improved Working Capital Management
- Demonstration Programs
- Rental Purchase Schemes
- Stock Programs

Programs are tailored by region through a panel of funders.

TFS offers a comprehensive suite of finance and leasing facilities for the end user.

The concept of adding value to your business is critical to us and this is why the TFS Team can assist you in developing the right solution for you.

These facilities can be developed and tailored to suit the individual needs of each customer.

We offer a wide range of facilities tailored by region:

- USA
- Canada
- EMEA
- JAPIC region

The range of facilities and services available are as follows;

- Leasing Solutions
- Operating lease Solutions
- Fair Market Value lease solutions
- Loans/Hire Purchase facilities
- Used Equipment Financing
- Asset Management



HEAD OFFICE

200 Coalisland Road,
Dungannon, Co. Tyrone,
Northern Ireland
BT714DR

Tel: +44 2887 718 500

Email: evoquip@terex.com

SOUTH

Terex India Private Limited
Plot No : E-18, Expansion-II, Phase-II
SIPCOT, Krishnagiri Road
Hosur - 635 109, Tamil Nadu

Tel: +91 4344 352 200

NORTH

Terex India Private Limited
907-908, 9th Floor, Palm Spring Plaza,
Golf Course Road, DLF Phase 5, Sector 54,
Gurgaon 122 003, Haryana

Tel: +91 4344 352 164

The material in this document is for information only and is subject to change without notice.
EvoQuip assumes no liability resulting from errors or omissions in this document, or from the use of the information contained herein.
Due to continual product development we reserve the right to change specifications without notice. Product performance figures given in this brochure are for guidance purposes only, this information does not constitute an expressed or implied warranty or guarantee, but shows test examples. These results will vary depending on application. Photographs are for illustrative purposes only; some or all of the machines in the illustrations may be fitted with optional extras. Please check with your Dealer for details on optional extras.
Published and Printed in February 2026. All machines are CE Approved.

© Terex Corporation 2026



terex.com/EvoQuip